Since monitored concentrations have remained well below established guidelines and New Indy must continue to report results from their required monitoring, DHEC will suspend facility boundary Hydrogen Sulfide monitoring and daily reporting in January 2024. Monitoring may resume if there is an increase in on-site monitored concentrations or a significant change in operations associated with potential odor sources.

Air Monitoring Summary Tables

EST

This table summarizes monitoring data collected using DHEC monitors and EPA's Viper wireless remote monitoring system.

Project Name: H2S in South Carolina

From: 1/6/24 To: 1/6/24 12:00 AM 11:59 PM

EST



Catawba Express							
Instrument	Analyte	ATSDR MRL Exceedance?	Number of Readings	Number of Detections	Concentration Range	Period Average	ATSDR MRL
SPM Flex 2	H2S	No	2881	236	0 - 7 ppb	0.23 ppb	70 ppb

Notes:

Hydrogen sulfide concentrations presented in this data summary table are converted from parts per million, the instrument readout units, to parts per billion. The SPM FLEX Minimum Detectable Limit (MDL) is 1 ppb of Hydrogen Sulfide.

ATSDR MRL Agency for Toxic Substances and Disease Registry Minimal Risk Level - Acute Exposure (<14 days)


H₂S Hydrogen Sulfide

hr Hour

ppb Parts per billion

MRL Exceedance Defines if the 24-hr TWA exceeded the MRL at any time during the period of this report

SPM Single Point Monitor
TWA Time Weighted Average



H₂S in South Carolina

Hydrogen Sulfide 15-min and 24-hr Time Weighted Average Graphs

Wind direction was variable. Through early afternoon, wind was from the north, southeast, then north northwest. By midafternoon, variability was reduced, with winds coming from the west, south southwest, and finally coming from the southwest by the end of the period.

